



# Warpp Cut GlyCool

Plasma Torch Coolant

5 Ltr  
@29.5 °C

### Product Description:

Warpp Cut GlyCool is a low-viscosity coolant for optimal heat transfer in plasma cutting torches. It meets the resistivity standards of most high-performance plasma torches. With advanced corrosion inhibitors and protective additives, Warpp Cut GlyCool safeguards cooling heads and cooling systems, ensuring compatibility with both metal and non-metallic components. It is non-volatile, non-hazardous, and particularly suited for plasma cutting systems.

### Directions for Use:

Thoroughly clean all metallic and rubber components of the cooling system before use.

Product is ready-to-use; DO NOT dilute.

NEVER mix with tap water, distilled water, mineral oils, lubricants, or anti-spatter compounds.

Best if used within 3 years from the date of manufacture.

### Caution:

Keep out of reach of children.

Avoid contact with eyes. In case of contact, rinse immediately with water.

Wash hands thoroughly after handling.

Maintain proper coolant line pressure before starting operations.

Use gloves to avoid skin contact.

### Storage:

Store in a cool, dry place away from direct sunlight.



**WARPP ENGINEERS**

Email : [Salesupport@warpp.co.in](mailto:Salesupport@warpp.co.in)

Phone : 8551817744 / 8551819944

Batch :

Mfg. Date :

M.R.P. :

(Inclusive of all taxes)





# Warpp Weld GlyCool

MIG/TIG/Laser Welding Torch Coolant

5 Ltr  
@29.5 °C

### Product Description:

WARPP Weld GlyCool is an economical, low-viscosity, low-toxicity, and non-combustible coolant specifically formulated for MIG, TIG, Laser welding torches, and other self-contained chiller units. It contains corrosion inhibitors that protect iron, steel, aluminum, brass, and copper components. Environmentally friendly and non-volatile, WARPP Weld GlyCool effectively prevents internal mineral deposits and clots, enhancing the performance and longevity of welding equipment.

### Directions for Use:

Thoroughly clean all metallic and rubber components of the cooling system before use.

Product is ready-to-use; DO NOT dilute.

NEVER mix with tap water, distilled water, mineral oils, lubricants, or anti-spatter compounds.

Best if used within 3 years from the date of manufacture.

### Caution:

Keep out of reach of children.

Avoid contact with eyes. In case of contact, rinse immediately with water.

Wash hands thoroughly after handling.

Maintain proper coolant line pressure before starting operations.

Use gloves to avoid skin contact.

### Storage:

Store in a cool, dry place away from direct sunlight.



**WARPP ENGINEERS**

Email : [Salesupport@warpp.co.in](mailto:Salesupport@warpp.co.in)

Phone : 8551817744 / 8551819944

Batch : .

Mfg. Date : .

M.R.P. : .

(Inclusive of all taxes)

