

## Technical Sheet

# Rubber Hose for Welding

**Applications** Recommended for use with welding and gas cutting in a workshop ship yards, construction sites and manufacturing Industries etc.

**Construction**

**Tube** Uniform in thickness made from a blend of Nitrile Rubber Compound

**Reinforcement** High Tensile Synthetic Yarn

**Cover** Natural Modified rubber, Wrap Finish.

**Temp-range** .-30°c. to +80°c.

**Colour** Blue or Black - for Oxygen & Non fuel gases, Red- for fuel gases and acetylene gases.

Part No.	ID		OD	Maximum Working Pressure		Minimum Burst Pressure		WT./Meter	STD. LENGTH
	MM	INCH	MM	PSI	BAR	PSI	BAR	KGS.	MTR.
	± .5mm		± .5mm						
GWH- 613	6.3	1/4	13	290	20	870	60	0.190	50 -100
GWH- 815	8.0	5/16	15	290	20	870	60	0.210	50 -100
GWH- 916	9.0	3/8	16.5	290	20	870	60	0.250	50 -100
GWH - 1220	12.5	1/2"	20	290	20	870	60	0.325	50 -100

**Raghunath Rubber Industries**



(Authorized Signatory)

**RAGHUNATH RUBBER INDUSTRIES**

📍 Dukheri Road, Mohra, Ambala Cantt (HR) Pincode-133004, (INDIA)  
 ✉ gangahoses@gmail.com

🌐 www.gangahoses.com

☎ +91-171-2871037, 2871137  
 📠 +91-171-2871137