

TECHNICAL SHEET

OIL RESISTANCE RUBBER HOSE (GSPR6)

Applications Oil Resistance rubber hose for low pressure hydraulic systems , Rape Seed, petroleum or poly glycol base oils, water & oil emulsions and water & drain oil lines..

Lining Oil resistant synthetic rubber.

Reinforcement One braid of textile yarn

Cover Synthetic rubber Resistant to oil, Weather, abrasion and ozone

Temp-range - 40°c to + 60°C

Inner & Cover

Colour Black

Brand Name GANGA

Item Code	ID (+0.5mm)		OD (+0.5mm)	Maximum Working Pressure		WT. per/mtr	STD. LENGTH
	INCH	MM		PSI	BAR		
GSPR 6- 612	1/4	6.30	12.30	400	28	0.150	50 - 100
GSPR 6- 814	5/16	8.00	14.50	400	28	0.200	50 - 100
GSPR 6 -1016	3/8	10.00	16.0	400	28	0.210	50 - 100
GSPR 6 -1220	1/2	12.70	20.0	400	28	0.300	50 - 100
GSPR 6 -1623	5/8	16.00	23.50	340	24	0.350	50 - 100
GSPR 6 - 1927	3/4	19.50	27.00	300	21	0.450	50 - 100
GSPR 6 -2231	7/8	22.00	31.00	300	21	0.600	50 - 100
GSPR 6 -2534	1	25.40	34.00	185	13	0.700	50 - 100
GSPR 6 -3241	1.1/4	32.00	41.00	140	10	1.000	40
GSPR 6 - 3851	1.1/2	38.50	51.00	140	10	1.200	40
GSPR 6 -5065	2	50.00	65.00	140	10	2.250	40

Thanks & Regards,

For Raghunath Rubber Industries

RAGHUNATH RUBBER INDUSTRIES

📍 Dukheri Road, Mohra, Ambala Cantt (HR) Pincode-133004, (INDIA)

✉ gangahoses@gmail.com

🌐 www.gangahoses.com

☎ +91-171-2871037, 2871137

📞 +91-171-2871137