

TECHNICAL SPECIFICATION
Rubber Hose for Air/Pneumatic
 As per IS 446 and ISO 2398

Applications Recommended for use with air compressors and other civil construction sites & Industrial applications.

Uniform in thickness made from a blend of natural & Synthetic Rubber Compound

Tube

High Tensile Synthetic Yarn

Reinforcement

Natural Modified rubber Abrasion and Ozone Resistant,

Cover

Wrap Finish

Finish

- 40° to + 70°

Temp-range

Inner- Black & Outer Cover - black

Colour

Part No.	ID		OD	Maximum Working Pressure		Minimum Burst Pressure		WT.	STD. LENGTH
	MM	INCH	MM	PSI	BAR	PSI	BAR	KGS.	MTR.
	± .5mm		± .5mm						
GAH- 613	6.0	1/4	13	300	20	900	60	0.180	50-100
GAH- 815	8.0	5/16	15	300	20	900	60	0.220	50-100
GAH- 916	9.5	3/8	16.5	300	20	900	60	0.260	50-100
GAH- 1220	12.5	1/2	20	300	20	900	60	0.350	50-100
GAH- 1627	16.0	5/8	27	300	20	900	60	0.500	50-100
GAH- 1929	19.0	3/4	29	300	20	900	60	0.700	50-100
GAH- 2536	25.0	1	36	300	20	900	60	0.900	50-100
GAH- 3143	32.0	1.1/4	43	300	20	900	60	1.300	40
GAH- 3850	38.0	1.1/2	50	300	20	900	60	1.400	40
GAH- 5065	50.0	2	65	300	20	900	60	2.250	40

Thanks & Regards,
For Raghunath Rubber Industries.

For Raghunath Rubber Industries
Authorized Signator

RAGHUNATH RUBBER INDUSTRIES