

## Technical Sheet

### Sand Shot Blasting Rubber Hose

**Application** Suitable for Conveying all commonly used material for blasting, such as steel shot, steel grit, garnet, copper stag, Coal slag, Aluminium oxide, Glass Breeds etc.

**Construction Tube** Synthetic & Natural Rubber blend resistant to abrasion.

**Reinforcement** Two braid of High Tensile Synthetic Yarn with anti-static Copper Flex Wire.

**Temp.** -40°C to + 80°C.

**Cover** Black, NR/ Cover-resistant to abrasion and weather.

**Properties** High abrasion resistance.

**Colour** Inner Tube- Black & Outer Cover- Black Wrap Finish.

**Applicable STD.** IS:5894, ISO-3861.

Part No.	ID		OD	Maximum Working Pressure		Minimum Burst Pressure		WT.	STD. LENGTH
	MM	INCH	MM	PSI	BAR	PSI	BAR	KGS.	MTR.
	± .5mm		± .5mm						
GSBH- 1227	12.5	1/2	27	174	12	522	36	0.550	50-100
GSBH- 1936	19.0	3/4	36	174	12	522	36	1.040	50-100
GSBH- 2543	25.0	1	45	174	12	522	36	1.440	50-100
GSBH- 3250	32.0	1.1/4	50.5	174	12	522	36	1.880	40
GSBH- 3858	38	1.1/2	58	174	12	522	36	2.010	40
GSBH- 5070	50	2	70	174	12	522	36	2.700	40

Regards,  
RAGHUNATH RUBBER INDUSTRIES

Authorized Signatory

### RAGHUNATH RUBBER INDUSTRIES

📍 Dukheri Road, Mohra, Ambala Cantt (HR) Pincode-133004, (INDIA)  
✉ gangahoses@gmail.com      🌐 www.gangahoses.com

☎ +91-171-2871037, 2871137  
📠 +91-171-2871137